

TOMBO NO. 9082 - PTFE THREAD SEAL TAPE

PREMIUM PINK PLUMBERS TAPE

a product of Nichias Corporation, Japan; a pioneer in the areas of Thermal Insulation and Gasket Materials



Every year, around 20 people in the UK die as a result of scalds caused by hot bath water.



Every year, a further 570 people in the UK suffer serious scald injuries caused by hot bath

Description

The **TOMBO Premium Pink Plumbers Tape** is designed for sealing threaded joints in general water systems and water heating systems. It is certified by DIN-DVGW* for usage in Hot Water up to 125°C and ≤ 7 bar in accordance to DIN EN 751-3, Class GRp.

The high density of the **TOMBO Premium Pink Plumbers Tape** conforms and holds the thread readily when wrapped around the specific threaded joint, reducing the occurrence of loose threads.

When properly applied, the **TOMBO Premium Pink Plumbers Tape** requires only 3 overlapping wraps to effect a leakproof joint**.

* DIN-DVGW registration no: NG-5143BR0385

** For poor quality or damaged threads that are hard to seal like parallel threads or threads on fittings subject to vibrations, more than 3 wraps may be necessary

Directions For Use



Exposure to water at 140°F for 5 seconds will result in third-degree burns. - Waller et al, 1993

1. Place end of **TOMBO Premium Pink Plumbers Tape** on pipe thread 1/8" (2mm) from end of pipe.
2. Wrap tape around pipe stretching slightly to pull tape into threads.
3. Slight overlap on the starting turn.
4. Cover all threads and pull hard to tear the tape.
5. Assemble joint.

Characteristic & Applications

- ✚ Provides tight seal; permits easy disassembly
- ✚ Flame resistant
- ✚ Colour coded 'PINK' for easy identification
- ✚ Compatible with a broad range of piping materials.
- ✚ Chemically inert and withstands solvents.
- ✚ Conformance to MIL SPEC A-A-58092

Product Specifications

Composition	: Min. 99.5% PTFE
Tape Colour	: Pink
Thickness	: 0.09mm (+/- 10%)
Density	: 1.2g/cm ³ (+/- 0.1g/cm ³)
Temp. Range	: -100°C ~ +260°C
Pressure Range	: For usage on pipe threads of liquid systems of 2,000psig or less.

Rev: 201106



NICHIAS FGS SDN BHD (Co. No. 203309 H)

Head office/Factory
Plot 103, Darulaman Industrial Estate
Bandar Darulaman, 06000 Jitra,
Kedah Darul Aman, Malaysia
Tel : 04-917 3760

Fax : 04-917 5964

Kuala Lumpur Sales Office
Lot 3, Lorong SS 13/3D, Subang Jaya
Industrial Area, Off Jalan SS 13/3, 47500
Subang Jaya, Selangor Darul Ehsan, Malaysia
Tel : 03-5636 4067 Fax : 03-5636 4078

